

Economical Washable Water Filters

Eliminate Costly Filter Changes



ADVANTAGES:

- Choice of plastic or metal mesh
- A quick rinse restores the filter
- 10" elements fit any standard housing without modification
- 5" & 20" housings and elements available upon request

APPLICATIONS:

- Machine Tool Coolant Lines
- Metalworking Fluids
- Plant Water Supplies
- Spray Nozzles
- Potable Water Systems
- Waste Water Systems



Keller Products
A DIVISION OF PLASTIC DESIGN, INC.

www.kellerfilters.com • info@kellerfilters.com
Phone: 1-800-352-8422 • Fax: (978) 264-0221

Specifications and Ordering Information

Filter Housings



Part Number	E050	E075	E100	E075ST	H075	H100
Port Size	1/2" NPTF	3/4" NPTF	1" NPTF	3/4" Stainless	3/4" NPTF	1" NPTF
Flow Rate (GPM)	15	15	15	15	20	20
Max. Pressure (PSIG)	100	100	100	100	100	100
Max. Temp. (°F)	100	100	100	100	175	175
Materials: Head	Polypro.	Polypro.	Polypro.	Polypro.	Nylon	Nylon
Materials: Bowl	PET	PET	PET	PET	Nylon	Nylon
Materials: O-Ring	EPDM	EPDM	EPDM	EPDM	EPDM	EPDM
No. Filter Element	1	1	1	1	1	1
Element Length	10"	10"	10"	10"	10"	10"

Filter Elements



Part Number	R10-7050	R10-7070	R10-4150	R10-4250	R10-5150	R10-5250
Filter Design	Plastic Net	Stainless Net	Stainless Net	Stainless Net	Stainless Pleated	Stainless Pleated
Filter Material	Polyester Fabric	316 SS	304 SS	304 SS	304 SS	304 SS
End Caps	Polypro.	Polypro.	None	None	None	None
Gaskets	SEBS	SEBS	BUNA	BUNA	BUNA	BUNA
Micron Rating	50	70	150	250	150	250
Maximum Temp. (°F)	100	100	275	275	275	275
Element Length	10"	10"	10"	10"	10"	10"

* Other micron sizes available upon request - Not for Potable Water Systems